



Consolidated Alloys

A Division of C.A. Group Australasia Pty. Limited inc in Vic.
ABN 83 005 084 097

www.cagroup.com.au

JUNE 2008

WEATHERFLASH

PRODUCT DESCRIPTION Weatherflash is a fully annealed, 99% pure uncoated aluminium flashing. It is impervious to moisture, malleable, tough and light weight.

APPLICATIONS Particularly suitable for use with colorbond® and zinalume® roofing. Can be used to protect timber exposed to severe weather and temperatures.
An ideal material for under doors and windows as well as on timber decking beams.
Also used for ant capping.

AVAILABLE FORMS

- Weatherflash is available in rolls
- Sizes available:

WIDTH	THICKNESS	LENGTH
150mm	0.30mm	10 and 20m
230mm	0.30mm	10 and 20m
300mm	0.30mm	10 and 20m
450mm	0.30mm	10 and 20m
150mm	0.45mm	10 and 20m
230mm	0.45mm	10 and 20m
300mm	0.45mm	10 and 20m
450mm	0.45mm	10 and 20m
150mm	0.70mm	10 and 20m
230mm	0.70mm	10 and 20m
300mm	0.70mm	10 and 20m
450mm	0.70mm	10 and 20m
600mm	0.70mm	10 and 20m

SPECIFICATION Conforms to the requirements of AS 2904:1995

THIS DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. CONSOLIDATED ALLOYS PROVIDES NO WARRANTIES, EITHER EXPRESSED OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. MATERIAL USE BEYOND THE CONTROL OF SUPPLIER

MELBOURNE (Head Office):
32 Industrial Avenue.
Thomastown, Vic. 3074
Telephone: (03) 9359 5811
Facsimile: (03) 9359 4076

SYDNEY:
5 Coates Place,
Wetherill Park, N.S.W. 2164
Telephone: (02) 9756 4011
Facsimile: (02) 9756 4074

BRISBANE:
Chrome Street,
Salisbury Nth, Qld. 4107
Telephone: (07) 3277 2977
Facsimile: (07) 3875 1994

PERTH:
1/19 Dowd Street,
Welshpool, W.A. 6106
Telephone: (08) 9353 4818
Facsimile: (08) 9353 4814

ADELAIDE:
Solder-Tech Pty. Ltd.
St Marys, S.A. 5042
Telephone: (08) 8276 8566
Facsimile: (08) 8276 9849

TASMANIA:
Wholesale Products Pty. Ltd.
Glenorchy, TAS. 7010
Telephone: (03) 6273 3455
Facsimile: (03) 6273 1901